

GZR Series



GOODSKY®
GOOD SKY ELECTRIC CO., LTD.

Application:

- ◆ Domestic Appliances, General Control
 - ◆ Dehumidifier
 - ◆ UPS

Features:

- ◆ High-capacity (25A) types available.
- ◆ 8 mm creepage / clearance.
- ◆ Slim size (28.8x12.7x25.5mm).
- ◆ Halogen Free series available

GZR

Performance Comparison with Competitors

GZR 性能比較表 (Performance Comparison List)								
品牌 Supplier		GOODSKY	OMRON	TYCO	Fujitsu	Song Chuan	HONGFA	
型號 Item		GZR	G2R-1-E	OZ	VSB	793	HF14FW	
Coil Type		VDC	VDC	VDC	VDC	VDC	VDC	
接點部 Contact Specs	開關型式 Contact Configuration	1A / 1C	1A / 1C	1A / 1C	1A / 1C	1A / 1B / 1C	1A / 1B / 1C	
	接點規格 Contact Rating	20A/277VAC 20A/30VDC 25A/125VAC 1HP 250VAC TV-10 120VAC	16A/30VDC 16A/250VAC	16A/30VDC 16A/240VAC	16A/30VDC 16A/250VAC	16A/30VDC 16A/250VAC	16A/24VDC 16A/277VAC	
	最大流通電流 Max. Allowable Current	25A	16A	16A	16A	16A	20A	
	最大承受電壓 Max. Allowable Voltage	380VAC 125VDC	380VAC 125VDC	240VAC 24VDC	250VAC 150VDC	250VAC	277VAC 30VDC	
線圈部 Coil Specs	額定電壓 Nominal Voltage(VDC)	3,5,6,9,12,15,18,24,48	5,6,12,24,48	5,6,9,12,24,48	3,5,6,9,12,14,18,24,36,48	3,5,6,9,12,18,24,48	5,6,9,12,18,24,48	
性能 Performance	接點阻抗 Contact Resistance	100mΩ	100mΩ	100mΩ	100mΩ	100mΩ	50mΩ	
	耐電壓(AC) Dielectric	I/O	5,000V	5,000V	5,000V	5,000V	5,000V	4,000V
		O/O	1,000V	1,000V	1,000V	1,000V	1,000V	1,000V
	壽命 Life Expectancy:	機械 Mechanical	10 ⁷	2 x 10 ⁷	10 ⁷	2 x 10 ⁷	10 ⁷	10 ⁷
		電氣 Electrical	10 ⁵	10 ⁵	10 ⁵	10 ⁵	10 ⁵	10 ⁵
安全規格 Safety Standard	UL & C-UL	VDE UL CSA SEV SEMKO	UL CSA TUV CQC	UL CSA VDE SEV FIMKO SEMKO OVE BSI	UL CSA TUV	CUL VDE CQC		
寸法 Dimension	外型尺寸 Dimension(mm)	28.8x12.7x25.5	28.8x12.7x25.3	29.2x12.8x20.6	29.2x12.9x25.3	29.5x13.5x26.0	29.0x13.0x26.5	
	重量 Weight(g)	17	17	13	18	17	18.5	