


RWH Series



Application:

- ◆ Domestic Appliances
- ◆ Audio Equipment
- ◆ Control Units
- ◆ Office Machines
- ◆ Coffeepot
- ◆ HVAC

Features:

- ◆ High switching current up to 15A in small size.
- ◆ Sugar-cube relay suitable for various applications.
- ◆ UL, C-UL & TUV safety standard approved.
- ◆ High adapt to harsh conditions with high temperature and vibration.
- ◆ In accordance with IEC 60335-1 Glow Wire requirement for home appliances.
- ◆ Comply with RoHS and REACH regulations.
- ◆ Halogen Free series available.

RWH

Performance Comparison with Competitors

RWH 性能比較表 (Performance Comparison List)							
品牌 Supplier		Goodsky	American Zettler	Omron	Panasonic	Hongfa	
型號 Model		RWH	AZ932	G5LA	JS	HF3FF	
線圈類型 Coil Type		DC	DC	DC	DC	DC	
接點 Contact Spec.	開關形式 Contact Form	1A/1B/1C	1A/1B/1C	1A/1C	1A/1C	1A/1C	
	接點規格 Contact Rating	12A/250VAC 15A/24VDC	15A/120VAC 15A/30VDC	10A/250VAC 10A/24VDC	10A/125VAC 5A/30VDC	10A/277VAC 10A/28VDC	
	最大流通電流 Max. Allowable Current	15A	15A	10A	10A	10A	
	最大承受電流 Max. Allowable Voltage	240VAC 110VDC	300VAC 30VDC	250VAC 24VDC	250VAC 100VDC	277VAC 28VDC	
線圈 Coil Spec.	額定電壓 Nominal Voltage	3,5,6,9,12 18,24,36,48	3,5,6,9,12, 18,24,48	5,9,12,24,48	5,6,9,12 18,24,48	5,6,9,12 18,24,48	
性能 Performance	接點阻抗 Contact Resistance		100mΩ	100mΩ	100mΩ	100mΩ	
	耐電壓 (AC) Dielectric	I/O	2000VAC	1500Vrms	2000VAC	2000VAC	1500VAC
		O/O	750VAC	1000Vrms	750VAC	750VAC	750VAC
	壽命 Expectancy	機械 Mechanical	10x10⁶	1x10 ⁶	10x10 ⁶	10x10 ⁶	10x10 ⁶
		電氣 Electrical	10x10⁴	10x10 ⁴	10x10 ⁴	10x10 ⁴	10x10 ⁴
	安全規範 Safety Standard		UL TUV	UL CUR	UL VDE	UL TUV, VDE	UL TUV, VDE
寸法 Dimension	外型 Dimension(mm)	19.0x15.4x 15.0	20.2x16.5x 20.2	19.6x15.6x 15.6	22.0x16.0x 16.0	19.0x15.2x 15.5	
	重量 Weight	9g	10g	7.5g	12g	10g	